

Nordic ID Merlin provides an efficient solution when a robust and multi-functional mobile computer is required. The physical keyboard of the mobile computer eases the use while working with gloves. Suitable application areas are for example manufacturing industries, retail business operations and logistics.



PRODUCT VARIANTS

NORDIC ID MERLIN
UHF RFID CROSS DIPOLE



NORDIC ID MERLIN
UHF RFID CROSS DIPOLE
ONE-SERIES



NORDIC ID MERLIN
UHF RFID



NORDIC ID MERLIN
HF RFID BLADE



NORDIC ID MERLIN
HF RFID



NORDIC ID MERLIN



UHF RFID



HF RFID



Laser
Barcode



2D Imager
Barcode



WLAN



3G



Blue-
tooth



GPS



Windows
CE6

UHF RFID IDENTIFICATION

Supported standard	ISO 18000-63 (EPC Class 1 Gen2 V2)
Frequency	ETSI 865.6 - 867.6 MHz or FCC/IC 902 - 928 MHz
Typical reading speed	200 tags per second (peak up to 400 tags per second)
NORDIC ID MERLIN UHF RFID Cross Dipole - One-series	RF Power: ERP +33 dBm (2W) (Only ETSI 865.6 - 867.6 MHz) Nominal reading distance: 7 m Software controlled antenna polarization, Horizontal, vertical or cross-polarized
NORDIC ID MERLIN UHF RFID Cross Dipole	RF Power: ERP +30 dBm (1W) Nominal reading distance: 5 m Software controlled antenna polarization, Horizontal, vertical or cross-polarized
NORDIC ID MERLIN UHF RFID	RF Power: ERP +27 dBm (0.5W) Nominal reading distance: 2.5 m Horizontal linear polarized

HF RFID IDENTIFICATION

Supported standard	Supported standard: ISO15693
Frequency	13.56MHz
Typical reading speed	Reading speed: up to 40 tags per second
NORDIC ID MERLIN HF RFID BLADE	RF Power: 1W Nominal reading distance: 0-40 cm
NORDIC ID MERLIN HF RFID	RF Power: 1W Nominal reading distance: 0-30 cm

BARCODE IDENTIFICATION

1D laser scanner	All major 1D bar codes Adaptive Auto-Range Laser (standard-, long- and auto-range) Normal, hold to aim and hold down modes Enhanced aiming mode (automatic switching between scan line / aiming dot) Configurable scan alert sounds
2D imager	All major 1D and 2D codes High visibility LED aimer 2 character pre and post fixes, padding, replacement Video preview Configurable scan alert sounds

PRODUCT HIGHLIGHTS

- Powerful mobile computer
- Fast and accurate reading
- Full day use with a single charge
- Sharp colour display

PREINSTALLED APPLICATIONS

- MICROSOFT APPLICATIONS:
- Internet Explorer web browser
 - Wordpad
 - Microsoft® Silverlight™
 - IE with Adobe® Flash® Lite

NORDIC ID APPLICATIONS:

- Display rotate
- Registry backup
- IP config
- Version tool
- NID Menu

CONTROL PANEL APPLET:

- NID Autostart: automatic start of application after network connection is established
- NID Backlight: backlight brightness
- NID Indicators: battery level and signal level indicators
- NID Backlight: keyboard & display brightness level
- NID Keypad: keyboard mapping
- NID LinkWatchdog: connection monitoring
- NID Menu: application manager
- NID Powerbutton: power button mapping
- NID Scanner: barcode type settings
- NID SNTP Service: network time synchronisation
- NID Touch screen: disable/enable
- NID Trigger button: Trigger button mapping
- NID WWAN settings

OPTIONAL APPLICATIONS

- Nordic ID Thin Client: RF-series emulation
- Naurtech CETerm: terminal emulation client

PLATFORM	
CPU	ARM11 532 MHz
Operating system	Microsoft® Windows® Embedded CE 6.0
Memory	256 MB DDR RAM 288 MB Flash (256 MB user accessible) microSD card slot (SDHC compatible)
USER INTERFACE	
Display	3,5" QVGA touch screen, 240 x 320 pixels, 262k colours Adjustable LED backlight, Daylight readable
Keypad	Numeric (alpha) keypad 29 distinguished buttons: 0-9 (alpha), scan, ok, del, tab, esc, shift, alt, 3 mode keys, 6 navigation keys Keyboard backlight with individual control for each key
Signals and indicators	Buzzer for audible signals (RTTTL support) Battery charging indicator LED Programmable LED
CONNECTIVITY	
Wireless WAN	3G UMTS / HSDPA (900/2100 MHz) GPRS / EDGE (900/1800 MHz) (optional)
GPS	Assisted GPS (optional)
Wireless LAN	IEEE 802.11 a/b/g/n
WLAN security	Standards: WEP, WPA, WPA2 (802.11i) Encryption: WEP, TKIP, AES
Wireless PAN	Bluetooth 2.0 + EDR, Class 2
LAN	Ethernet 10/100 via charger (optional)
PAN	USB via charger
POWER	
Battery	Rechargeable, removable Lithium-Ion battery pack 2600 mAh @ 7.4V 4800 mAh @ 7.4V with pistol grip Up to 30 h in intensive use (standard battery)
Charging	Desktop charging cradle with USB connection Desktop charging cradle with spare battery charging slot Typical charging time: 2,5 h (0 to 90 %) and 5 h (0 to 100 %)
External power supply	AC adapter for desktop charger: input 100-240 VAC, 1A, 50-60 Hz / output 24 VDC, 1.3A, 31.2 W / Power cable for EU, UK or US
Backup battery / batteries	Back-up battery for RAM: maintains memory contents for 8 hours Back-up battery for real-time clock: keeps time for 200 days
SIZE AND WEIGHT	
Dimensions	Nordic ID Merlin UHF RFID Cross Dipole (H) 250 x (W) 105 x (D) 175 mm Nordic ID Merlin UHF RFID (H) 250 x (W) 90 x (D) 47 mm Nordic ID Merlin HF RFID Blade (H) 340 x (W) 105 x (D) 265 mm Nordic ID Merlin HF RFID (H) 250 x (W) 90 x (D) 47 mm Nordic ID Merlin (H) 230 x (W) 90 x (D) 47 mm
Weight	Nordic ID Merlin UHF RFID Cross Dipole ~ 750 g Nordic ID Merlin UHF RFID ~ 550 g Nordic ID Merlin HF RFID Blade ~ 750 g Nordic ID Merlin HF RFID ~ 550 g Nordic ID Merlin ~ 450 g
DROP AND SHOCK	
Drop and impact resistance (drops onto concrete)	1.6 m (all except HF RFID Blade: 1.2 m)
Tumble	0,5 m ~500 tumbles (all except HF RFID Blade: n/a) 1 m ~250 tumbles (all except HF RFID Blade: n/a)
ESD	Contacts +/- 4kVdc Air discharge +/- 8kVdc
ENVIRONMENT	
Environmental sealing	IP54 - dust and water splash protected (all except HF RFID Blade: n/a)
Temperature	Operating -20° to +55° C Storage -20° to +60° C Charging 0° to +45° C
Relative humidity	10% to 95% non-condensing

- Naurtech SAP browser
- Netop remote management

SOFTWARE DEVELOPMENT ENVIRONMENT

FOR ALL DEVELOPERS:

- Microsoft Visual Studio 2005 and 2008
- Nordic ID MHL hardware abstraction layer
- Nordic ID UHF RFID API
- Nordic ID Sample applications and source code
- Nordic ID Customizer

FOR .NET (C#, VB ETC)

- .NET Compact Framework 2.0 and 3.5
- MHL API wrapper for .NET
- NUR API .NET
- OpenCF .NET - Smart Device Framework

FOR C++

- NUR API
- MHL API

FOR HTML

- Nordic ID Sample applications

ENVIRONMENT

- Free support during and after 2 year warranty time
- Maintenance service and extended maintenance contract
- Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

All information is subject to change without prior notice.



NORDIC ID HEADQUARTERS

Myllyjokankatu 2 A
FI-24100 Salo
FINLAND
tel. +358 2 727 7700
fax +358 2 727 7720
info@nordicid.com
www.nordicid.com

GERMANY

Nordic ID GmbH
Bielefeld, Germany
tel. +49 521/557717-0
fax +49 521/557717-10
info@nordicid.de
www.nordicid.de

BENELUX

Alphen aan den Rijn
The Netherlands
tel. +31 172 233 097
fax +31 172 475 653
info@nordicid.nl
www.nordicid.nl

V1013

